

GESSNER - WALKER DOUBLE DISK PLANTER



Parallelogram head easily mounts to 100mm x 100mm bar. Other bar sizes by special order.

Press wheel adjustment is so easy – with the simple spring loaded locking pawl.



Spring pressure adjustment easily made via pin placement.

Twin tapered bearing on each coultter. The carrier plates are easily removed for maintenance.



Three point linkage machines built to your requirements – Trailed machines from 3 to 7 beds or broadacre planter units to 18 metres.



Gessner Walker parallelogram double disc features the same unique bearing and sealing arrangement as the triple disc ensuring trouble free working, season after season.

GESSNER - WALKER



Unique combination sealing arrangement in coulter and press wheel alike ensures extra long bearing life.



Press wheels feature heavy duty hubs with the same sealing arrangements as the coulter. Positive easy to adjust depth control via the press wheel. Soft medium and hard rubber.



Independently sprung front coulter. Maintains planting depth even if the front coulter jumps.

508mm front coulter, 457mm double coulters are the perfect combination to ensure positive placement of seed and fertiliser. Front coulter runs off the plant line to avoid fertiliser burn.



Purchase single row units to mount to your own bar. 150mm x 100mm or 100mm x 100mm.



Three point linkage machines built to your requirements. Trailed machines from 3 to 7 beds or even broadacre planter units up to 18 metres.



GESSNER - WALKER

GESSNER INDUSTRIES