

- Used to build and renovate beds. The Triple Disc Hiller offers effective trash and chemical incorporation in tillage applications.
- Available to fit 178mm x 178mm toolbars and easily fitted to other size bars.
- Simple breast cut and undercut adjustment.
- Complete machines include Heavy Duty Cat 3 Hitch, Double Toolbar, Gauge Wheels, Support Stands and 600mm Bar Spacers.
- Each gang includes two self aligning greasable bearings on a 38mm square axle with one 558mm, one 508mm and one 457mm scalloped disc blade spaced 200mm apart. Attaching clamps and bolts to suit 178mm x 178mm bar included.
- 8 row rig includes 178mm x 178mm overbeam with 150mm spacers.
- 4 and 6 row units are fitted with Medium Duty Gauge Wheels.



- 8 row units are fitted with Heavy Duty Gauge Wheels.
- Requires approximately 25HP per row.

SPECIFICATIONS	ONE PAIR TRIPLE DISC HILLERS ONLY	COMPLETE 4 ROW MACHINE	COMPLETE 6 ROW MACHINE	COMPLETE 8 ROW MACHINE
PAIR OF HILLERS	1	4	6	8
178mm x 178mm x 9.5mm DUAL TOOLBARS	-	4.8m	6.8m	8.8m
OVERBEAM -178mm x 178mm x 9.5mm WITH FOUR 150mm SPACERS	-	NO	NO	YES
BAR SPACERS 600mm LONG 800mm OPTIONAL	-	3	4	6
GAUGE WHEELS (1 PAIR ADJUSTABLE AS STANDARD)	-	MEDIUM DUTY 7.50 x 16	MEDIUM DUTY 7.50 x16	HEAVY DUTY 1100 x 16
H.P. (DEPENDING ON SOIL TYPE)	25	100	150	200
WEIGHT - kg	280	2250	3000	4000
HITCH		CAT 3 MEDIUM DUTY WITH 4 MOUNTING BRACKETS	HEAVY DUTY CAT 3 WITH 6 MOUNTING BRACKETS	HEAVY DUTY CAT 3 WITH 6 MOUNTING BRACKETS
OPTIONAL ALABAMA KIT				

- Used to build and renovate hills and beds.
- Available to fit 178mm x 178mm tool bars and easily fitted to other size bars.
- 610mm scalloped discs.
- Fully adjustable for breast cut, undercut, and depth.
- Extra heavy duty construction.
- Double tapered roller bearing.
- Triple lip seal and felt dirt seal.
- Complete machines include Heavy Duty Cat 3 Hitch, Double Tool Bar, 600mm Bar Spacers, Gauge Wheels and Transport Stands.
- 8 Row machine includes 178mm x 178mm x 9.5mm Bridge.
- 8 Row machine fitted with Heavy Duty Gauge Wheels.
- 4 and 6 row machines are fitted with Medium Duty Gauge Wheels.
- Approximate HP requirement 20-30 HP per row.



Description	Approx. Wt.
One Pair of Disc Hillers complete with Mounting Brackets & Hardware on 610mm Scalloped Disc	250kg
Complete 4 Row Hiller (Standard 1metre Spacing)	1900kg
Complete 6 Row Hiller (Standard 1metre Spacing)	2500kg
Complete 8 Row Hiller (Standard 1metre Spacing)	3500kg



COMPLETE MACHINES INCLUDE HEAVY DUTY CAT 3 QUICK HITCH

THREE 178mm x 178mm x 9.5mm TOOLBAR.

This unit is used to build and renovate hills and beds. The ripper hiller can be fitted with hoe blades and fertilizer tubes to enable one pass bed preparation.

- Rippers are manufactured from high grade Bisalloy steel and have replaceable points and shin guards.
- 610mm scalloped discs.
- Fully adjustable breast cut, undercut and depth.
- Extra heavy duty construction.
- Double tapered roller bearings
- Triple lip seal and felt dirt seal.
- 8 row machine includes 178mm x 178mm x 9.5mm bridge.
- 8 row machine is fitted with heavy duty gauge wheels.
- 4 and 6 row machines are fitted with medium duty gauge wheels.
- Approximate HP requirement - 30-40 HP per row.

Description	Approx. Wt.
One pair of Disc Hillers complete with Mounting Brackets and Hardware	250kg
One Mini Ripper Assembly complete with Mounting Brackets and Hardware	59kg
Complete 4 Row Ripper Hiller (Standard 1 metre spacing)	2550kg
Complete 6 Row Ripper Hiller (Standard 1 metre spacing)	3400kg
Complete 8 Row Ripper Hiller (Standard 1 metre spacing)	4300kg