

- Used to build and renovate beds. The Triple Disc Hiller offers effective trash and chemical incorporation in tillage applications.
- Available to fit 178mm x 178mm toolbars and easily fitted to other size bars.
- Simple breast cut and undercut adjustment.
- Complete machines include Heavy Duty Cat 3 Hitch, Double Toolbar, Gauge Wheels, Support Stands and 600mm Bar Spacers.
- Each gang includes two self aligning greasable bearings on a 38mm square axle with one 558mm, one 508mm and one 457mm scalloped disc blade spaced 200mm apart. Attaching clamps and bolts to suit 178mm x 178mm bar included.
- 8 row rig includes 178mm x 178mm overbeam with 150mm spacers.
- 4 and 6 row units are fitted with Medium Duty Gauge Wheels.



- 8 row units are fitted with Heavy Duty Gauge Wheels.
- Requires approximately 25HP per row.

SPECIFICATIONS	ONE PAIR TRIPLE DISC HILLERS ONLY	COMPLETE 4 ROW MACHINE	COMPLETE 6 ROW MACHINE	COMPLETE 8 ROW MACHINE
PAIR OF HILLERS	1	4	6	8
178mm x 178mm x 9.5mm DUAL TOOLBARS	-	4.8m	6.8m	8.8m
OVERBEAM -178mm x 178mm x 9.5mm WITH FOUR 150mm SPACERS	-	NO	NO	YES
BAR SPACERS 600mm LONG 800mm OPTIONAL	-	3	4	6
GAUGE WHEELS (1 PAIR ADJUSTABLE AS STANDARD)	-	MEDIUM DUTY 7.50 x 16	MEDIUM DUTY 7.50 x 16	HEAVY DUTY 1100 x 16
H.P. (DEPENDING ON SOIL TYPE)	25	100	150	200
WEIGHT - kg	280	2250	3000	4000
HITCH		CAT 3 MEDIUM DUTY WITH 4 MOUNTING BRACKETS	HEAVY DUTY CAT 3 WITH 6 MOUNTING BRACKETS	HEAVY DUTY CAT 3 WITH 6 MOUNTING BRACKETS
OPTIONAL ALABAMA KIT				