

# LANDMASTER



The Gessner Landmaster can be configured to suit a range of applications, catering for all of your Broadacre planting requirements. Standard Landmaster configurations range from 12m to 24m featuring tyne spacing ranging from 333mm to 500mm. In addition, custom configurations are available to ensure that all of your planting needs are catered for.

Heavy duty 3-Bar Gessner frames constructed from 100 x 100 x 9 RHS or 178 x 178 x 9 RHS provide the Landmaster with unmatched strength and durability in the field. Frames also feature optional hydraulic single fold and double fold configurations, making the Landmaster easily transportable between working areas.

Various linkage options are available depending on machine size and customer specifications, including three point linkage for smaller machines, and floating trailing hitches applicable to all models.

The durable frame design, coupled with premium customisable attachments and after sales service which is second-to-none, makes the Gessner Landmaster your number one choice for Broadacre planting solutions.



## PARALLELOGRAM TYNE

- Parallelogram units feature robust 50 x 25mm spring steel tynes with a working depth range of 25 – 200mm.
- Tyne depths are easily adjusted in 12mm increments.
- Manutec press wheel assemblies are available in a range of profiles and diameters. Fixed or swivel mounting options for press wheels are available.
- True parallelogram action is provided with ground following capabilities via 14" rubber banded depth wheels fitted to 20" coulters.
- All pivot points are fitted with chrome pins and oil infused bushes.
- Heavy duty jump cylinders with high quality hard chrome shafts provide units with strength and durability.
- Parallelogram down pressure can be easily adjusted by moving the ergonomic hand grip through incremental pin points. Down pressure increments range from 20kg – 250kg.



