

RHIINO RIPPER

Gessner Rhino Rippers are renowned for their strength and durability in the field. By harnessing proven manufacturing processes and utilising the highest quality materials Gessner offers the ultimate in deep tillage solutions for various applications.

PRODUCT FEATURES:

- Super strong 250mm x 150mm x 10mm main beam.
- 5 and 7 shank machines are available in both three point linkage and trailing hitch options.
- 9, 11 and 13 shank machines are trailing only
- 5 shank machines feature 7.50 x 16 single compactors.
- 7 shank machines feature 7.50 x 16 dual compaction.
- 9, 11 and 13 shank machines feature 9.00 x 20 dual compactors.
- Hydraulic top-link levelling.

OPTIONAL EXTRAS:

- Hydraulic crumble rollers available to suit all models.
- Extension kits available.

RHINO SHANKS

- 32mm high-tensile shanks with 10 tonne breakout force.
- Shanks feature replaceable high wearing shin guards.
- 500mm spacing.
- 36" (914mm) underframe clearance.



MODEL	7 SHANK	9 SHANK	11 SHANK	11 SHANK - RC	13 SHANK
Approx HP Requirement	300-350HP	350-450HP	400-500HP	400-500HP	450+HP
Tyne Spacing	500mm (20")	500mm (20")	500mm (20")	545mm (21.5")	500mm (20")
Effective Working Width	3.5m	4.5m	5.5m	6m	6.5m
Approx Weight - No Roller	3,110kg	3,780kg	4,580kg	4,690kg	5,390kg
Approx Weight - C/W Roller	3,850kg	4,760kg	5,730kg	5,940kg	6,740kg
Transport Width - No Roller	3,450kg	4,250kg	5,250kg	5,850kg	6,250kg
Transport Width - C/W Roller	4,040mm	5,100mm	6,100mm	6,700mm	7,100mm
Wheel & Tyres	2 Pair 7.50x 16 Duals	2 Pair 9.00 x 20 Duals			
Crumble Roller (Optional)	Ø457 Heavy Wall Pipe fitted with 50 x 12 Flats to break down Clods				
Tynes	32mm x400GR High Tensile Plate with replacable shin guard & Tungsten Hardfaced point				
Under Frame Clearance	915mm (36")				
Hydraulic Breakout Force	10,000kg (22,000lb)				